## **MEDIUM DUTY SEWING MACHINES FOR SAILS...**



LONG ARM Underarm clearance 735x120mm





FM9518-30-17

### LONG & HIGH ARM Underarm clearance 735x170mm

## ... THE PRACTICAL SEWING SOLUTION FOR SURFING SAILS, SPINNAKERS AND LIGHT-MEDIUM SAILS

THIS ARM IS FACTORY CAST FOR STRENGHT & STABILITY (NOT A CUT AND PIECE EXTENDED ARM), TO AVOID VIBRATION AND NOISE EVEN SEWING HEAVY BOAT SAILS.

THE MACHINE IS MODIFIED, ALSO IN THE STRUCTURE BODY IN OUR WORKSHOP, AND PREPARED WITH SPECIAL SETTINGS FOR SAILMAKERS.

IT EMPLOYS A PARALLEL VERTICAL NEEDLE BAR MOTION FOR STRONGER STRIKING POWER AND A SEMI-AUTOMATIC LUBRIFICATION SYSTEM WHICH IMPROVES THE SERVICE LIFE.

THE STITCH LENGTH UP TO 5mm AND ZIG-ZAG WIDTH OF MAX. 10mm, ALL COMMON OPERATIONS ON MODERN SAILS CAN BE REALIZED.

#### **MACHINE FEATURES:**

NEW SEWING MACHINE FOR MEDIUM DUTY, 1 NEEDLE NEEDLE SYSTEM 134-35 SIZE 90-130, BIG ROTARY HOOK, SPEED MAX 1200/1400 STITCH PER MINUTE, THREAD MINIMUM V46 to V138 MAX STITCH LENGTH : 5mm ZIG-ZAG WIDTH : FROM 4.5 to 10mm FOR ZIG-ZAG STITCHES INTERCHANGEABLE CAMS FOR ZIG-ZAG, THREE-STITCH FROM 0 TO 12MM, SPECIFIC CAM FOR STRAIGHT STITCH STAND, 60MM SPECIAL THICK HEAVY TABLE TOP, 220/380V CLUCHT MOTOR or 220V ELECTRONIC MOTOR

#### WARRANTY :

24 MOUTHS FOR DEFECTIVE QUALITY PARTS, EXCLUDED REAR PARTS. FREE WORKING TIME FOR 12 MONTHS.



#### **AVAILABLE 2 DIFFERENT EQUIPMENTS:**

- BASE MACHINE EQUIPPED WITH STAND, TABLE AND CLUTCH MOTOR
- "AU" VERSIONS : EQUIPPED WITH ORIGINAL PNEUMATIC PULLER, THREAD TRIMMER, PNEUMATIC FOOTLIFTING, PNEUMATIC REVERSE, STAND TABLE AND ELECTRONIC MOTOR 220v

**OPTIONAL PULLERS:** 



DT PULLER economic puller with rollers, double traction top and bottom



**BELT PULLER** by FERRARI MARIO

with 50mm wide vertical pneumatic powerfull belt, FREE LOWER ROLLER in the table top, pneumatic pressure and 50mm lift



**DT-BELT PULLER** by FERRARI MARIO

with 50mm wide vertical pneumatic powerfull belt, DRIVEN LOWER roller in the table top, pneumatic pressure and 50mm lift

SPECIAL HIGH REINFORCED FIXING, and SPECIAL CONNECTIONS BETWEEN SEWING BARS AND PULLER GROUP FOR ELIMINATE BENDING

#### AVAILABLE 26cm SHORT ARM MACHINE FOR 8mm THICKNESS

Specifications	Max speed	Presser foot lift	Stitch length	Zig-zag width	Needle system	Thead size	Working area
9518-30	1400	7mm manual 12mm pneumatic	0 – 5 mm	Zig-zag / three- stitch 4,5-10mm.	134-35	From V46 to V138	735 x 120mm
9518-30-17	1200			Straight stitch by spedific cam	100-140		735 x 170mm

# EUROPEAN DISTRIBUTOR

Special sewing for sailmaking, cutting tables, accessories Via E.Fermi, 16 25013 Carpenedolo – BS – Italy Tel / Fax +39 0309965924 Mobile Mario 3339504256 Mobile Simone 3355263265 www.ferrarimario.it ferrarimaccucire@tiscali.it