MEDIUM DUTY SEWING MACHINES FOR SAILS...

FM9518



FM9518-30 Long arm 735x115mm

FM9518-30-17 Long & High arm 735x165mm



... THE PRACTICAL SEWING SOLUTION FOR SURFING SAILS,
SPINNAKERS AND LIGHT-MEDIUM SAILS

THIS ARM IS THE ONLY BUILDING WITH FACTORY CAST
FOR STRENGTH & STABILITY (NOT A CUT AND PIECE EXTENDED ARM).
THIS MEANS IS A UNIQUE PIECE OF CAST IRON WITHOUT ANY WELDING LINE.
THE HIGH THICKNESS OF THE FACTORY CAST UP TO 10mm AND INTERNAL
REINFORCEMENTS MAKE MACHINE STRONG ENOUGHT FOR USE FROM SPINNAKER
TO 8/9mm SAILCLOTH (DEPEND OF MATERIAL)

THE MACHINE IS MODIFIED, IN OUR WORKSHOP, AND PREPARED WITH SPECIAL SETTINGS FOR SAILMAKERS.

THE PNEUMATIC SYSTEM IS ON THE HEAD FOR EASY MANITEINANCE AND FOR REDUCE CABLES UNDER THE TABLE TOP. INTEGRATED COMMANDS INTO THE HEAD IN FRONT OF THE OPERATOR FOR EXTERMELY EASY HANDLING.

IT EMPLOYS A PARALLEL VERTICAL NEEDLE BAR MOTION FOR STRONGER STRIKING POWER AND A SEMI-AUTOMATIC LUBRIFICATION SYSTEM WHICH IMPROVES THE SERVICE LIFE.

THE STITCH LENGTH UP TO 5MM AND ZIG-ZAG WIDTH OF MAX. 10MM, ALL COMMON OPERATIONS ON MODERN SAILS CAN BE REALIZED WITH THE COMFORTABLE INTEGRATED CONTROLS IN THE HEAD REACH OF THE OPERATOR

MACHINE FEATURES:

NEW SEWING MACHINE FOR MEDIUM DUTY. 1 NEEDLE

NEEDLE SYSTEM 134-35 SIZE 90-130, BIG ROTARY HOOK, SPEED MAX 1200/1400 STITCH PER MINUTE, THREAD MINIMUM V46 to V138

MAX STITCH LENGTH: 5mm

ZIG-ZAG WIDTH: FROM 4.5 to 10mm FOR ZIG-ZAG STITCHES

INTERCHANGEABLE CAMS FOR ZIG-ZAG, THREE-STITCH FROM 4,5 TO 10mm, SPECIFIC CAM FOR STRAIGHT STITCH

STAND, 60MM SPECIAL THICK HEAVY TABLE TOP, 220/380V CLUCHT MOTOR or 220V ELECTRONIC MOTOR

WARRANTY:

24 MOUTHS FOR DEFECTIVE QUALITY PARTS, EXCLUDED REAR PARTS. FREE WORKING TIME FOR 12 MOUTHS.

Available 2 different equipments:

- Base machine equipped with stand, table and clutch motor
- "AUT" versions: pneumatic pressure of the foot and 15mm footlifting, pneumatic reverse by push, heavy duty stand with regolable height and castors, 60mm thick table top and electronic motor 220v

Optional pullers:

Simple original pneumatic puller with upper roller for light works

Alternative powerfull pullers :



DT puller
Economic puller with rollers, double traction top and bottom



Belt puller by Ferrari Mario
With 50mm wide vertical
Pneumatic powerfull belt,
Free lower roller in the table top, pneumatic
pressure and 50mm lift



DT-belt puller by Ferrari Mario
With 50mm wide vertical
Pneumatic powerfull belt,
Driven lower roller in the table top, pneumatic
pressure and 50mm lift

Special high reinforced fixing, and special connections between sewing bars and puller group for eliminate bending

Specifications	Max speed	Presser foot lift	Stitch length	Zig-zag width	Needle system	Thead size	Working area
9518-30	1200	7mm manual 15mm pneumatic	0 – 5 mm	Zig-zag / three- stitch 4,5-10mm.	134-35	From V46 to V138	735 x 115mm
9518-30-17	1000			Straight stitch by specific cam	100-140		735 x 165mm

FERRARI MARIO

Special sewing machines for sailmaking, cutting tables, accessories
Via E.Fermi, 16 25013 Carpenedolo – BS – Italy

Tel / Fax +39 0309965924

Mobile Mario 3339504256 Mobile Simone 3355263265

www.ferrarimario.it ferrarimaccucire@tiscali.it